



Minivet 600 – 1000 VA Line Interactive UPS

From The Leading Japanese UPS Company

Applications

Wi-Fi Routers | CCTV Systems | Servers | Computers | Modems

Technical Specification

Model	Minivet 600	Minivet 1000
Capacity	600VA/360W	1000VA/600W
Input		
Voltage	220/240 VAC	
Voltage Range	140-300 VAC	
Frequency Range	50 Hz	
Output		
AC Voltage Regulation (Batt. Mode)	±10%	
Frequency Range (Batt. Mode)	50 Hz ±1 Hz	
Transfer Time	Typical 4-8 ms	
Waveform (Batt. Mode)	Simulated Sine Wave	
Battery		
Battery Connection	Internal	
No. of Battery	12V, 1 No	12V, 2 Nos
Charging Current	1 A	1 A
Battery Capacity used	7AH	7AH
Typical Recharge Time	4 – 6 hours up to 90% capacity	

Indicators		
AC Mode	Green Lighting	
Battery Mode	Yellow Flashing	
Fault	Red Lighting	
Alarm		
Low Battery	Sounds Every Second	
Overload	Sounds Every 0.5 Second	
Fault	Continuous Sound	
Protection		
Full Protection	Overload, Discharge and Overcharge Protection	
Physical		
Dimension, D X W X H (mm)	279 x 101 x 142	320 x 132x 182
Net Weight (kg)	4.4	7.8
Environment		
Humidity	0-90 % RH @ 0-40°C (Non-Condensing)	
Noise Level	Less than 40dB	

Fuji Electric India

+91 85959 55400 support.li@fujielectric.com www.india.fujielectric.com